



## Section 1 Identification

**Trade Name:** Instant Power Heavy Duty Foaming Degreaser  
**Product Identification:** 2102  
**Synonyms:** Water-based alkali detergent  
**Product UseDescription:** Cleaner / Degreaser

**General Info Phone:** (800) 334-2077  
**Emergency Phone:** (800) 424-9300 (CHEMTREC)

**Supplier:**  
Instant Power Corporation  
1255 Viceroy  
Dallas, Texas 75247  
[www.myinstantpower.com](http://www.myinstantpower.com)  
[mail@myinstantpower.com](mailto:mail@myinstantpower.com)

## Section 2 Hazards Identification

### Classifications

Skin corrosion


- Category 1

Eye Damage -

Category 1

Skin Sensitization - Category 1

Gasses under pressure - Liquefied gas



Compressed Gas

Corrosive

Irritant

**Signal Word:** Danger

### Hazard Statements

Keep out of reach of children. Read label and SDS before use.

May cause severe skin burns and eye damage

Contains gas under pressure; may explode if heated.

May cause an allergic skin reaction.

### Precautionary Statements

#### Prevention

Do not breathe mists.

Wash hands thoroughly after handling.

Wear protective gloves and clothing.

Wear eye and faceprotection.

Contaminated work clothing must not be allowed out of the workplace.

Keep away from heat, sparks, open flames and hot surfaces. -No smoking. Pressurized container:

Do not pierce or burn, even after use.

**Response**

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.  
 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with soap and water/shower. Wash contaminated clothing before reuse.  
 If skin irritation or rash occurs: Get medical attention.  
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 Immediately call a poison center or a physician.  
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 Immediately call a poison center or a physician

**Storage**

Protect from sunlight. Store in a well-ventilated place.  
 Do not expose to temperatures exceeding 50 °C/ 122 °F.  
 Store locked up.

**Disposal**

Dispose of contents and container in accordance with all local, regional, and national regulations.

**Hazards Not Otherwise Specified**

Not applicable

**Section 3 Composition**

Chemical Name	CAS #	Concentration % by Weight
2-butoxyethanol	111-76-2	>=1 <= 5
D-limonene	5989-27-5	>=1 <= 5
Propane	74-98-6	>=1 <= 5
Butane	106-97-8	>=1 <= 5
Sodium Metasilicate	6834-92-0	<= 1

**Section 4 First Aid**

**EMERGENCY OVERVIEW**

**DANGER.** May be harmful if swallowed. May cause severe skin burns and eye damage.

**EYES:** Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. Immediately call a poison center or a physician.  
**SKIN:** Take off immediately all contaminated clothing and wash it before reuse. Wash with plenty of soap and water/shower. If skin irritation persists get medical attention.  
**INHALATION:** Remove person to fresh air and keep comfortable for breathing. Immediately call a poison center or a doctor.  
**INGESTION:** Rinse mouth. Do not induce vomiting. Seek medical attention immediately.

**Section 5 Fire Fighting Measures**

**Suitable fire extinguishing media:**

Use water spray, fog or foam.

**Specific hazards arising from the chemical:**

In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of subsequent explosion. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion. Bursting aerosol containers may be propelled from a fire at high speed.

**Hazardous thermal decomposition products:**

Carbon Dioxide, Carbon Monoxide

**Specific fire-fighting methods:**

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

**Special protective equipment for fire fighters:**

Fire fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in a positive pressure mode.

## Section 6 Accidental Release Measures

**Personal precautions:**

Put on appropriate personal protective equipment (see section 8)

**Environmental precautions and clean-up methods:**

Stop all leaks. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Eliminate all ignition sources. Disperse vapors with water spray. Prevent runoff from entering drains, sewers, streams or other bodies of water. Absorb spill with inert material. Absorb unrecoverable product. Transfer contaminated absorbent, soil and other materials to containers for disposal.

## Section 7 Handling and Storage

Do not use or store near heat, sparks or open flame. Exposure to temperatures above 120 F may cause bursting. Do not puncture or incinerate container. Store in a cool, dry place. Do not get in eyes, on skin or on clothing. Intentional misuse by deliberately concentrating and inhaling may be harmful or fatal. Keep out of reach of children.

## Section 8 Exposure Controls/Personal Protection

2-butoxyethanol	
ACGIH TLV	20 ppm
OSHA PEL	25 ppm (skin)
Propane	
ACGIH TLV	1000 ppm
Sodium Metasilicate	
ACGIH TLV	10 mg/m3
OSHA PEL	15 mg/m3

**Eye Protection:** Wear safety glasses or goggles.

**Skin Protection:** To prevent repeated or prolonged contact, wear impervious gloves (made from rubber, nitrile or neoprene).

**Respiratory Protection:** When respiratory protection is required use an organic vapor cartridge. A respiratory program that meets OSHA's 29 CFR 1910.34 & ANSI Z88.2 requirements must be followed.

**Engineering Controls:** Good general ventilation required.

## Section 9 Physical and Chemical Properties

Property	Value		
Appearance	CLEAR SPRAY	Auto Ignition Temp	Not Determined
Boiling Point	Not Determined	Color	Colorless
Decomposition Temperature	Not Determined	Evaporation Rate	Not Determined
Explosive Limit Ranges	Not Determined	Explosive Properties	Not Determined
Flash Point	Not Determined	Melting/Freezing Point	Not Determined
Odor	CITRUS	Odor Threshold	Not Determined
Other Information	VOC content (wt. %): 8.9	Oxidizing Properties	
Partition Coeff	Not Determined	Physical State	LIQUID
Relative Density	1.0	Solubility (Water)	COMPLETE
Vapor Density	Not Determined	Vapor Pressure	NOT AVAILABLE
Viscosity	Not Determined	pH	12-13

## Section 10 Stability and Reactivity

<b>Reactivity :</b>	Under normal conditions of storage and use, hazardous reactions will not occur.
<b>Chemical Stability :</b>	Stable under normal conditions.
<b>Incompatible Materials :</b>	Acids and strong oxidizers
<b>Conditions to Avoid :</b>	High temperatures, open flames, sparks, welding.
<b>Decomposition Products:</b>	CO, CO2

## Section 11 Toxicological Information

**Primary Route of Entry:** Skin contact, eye contact, inhalation

**Acute/Potential Health Effects:**

**EYES:** May cause severe irritation experienced as discomfort or pain, excess blinking and tear production, with redness and swelling of the conjunctiva.

**SKIN:** Brief contact may cause slight irritation. Prolonged contact may cause more severe irritation with pain, local redness and swelling, possible tissue destruction, and sensitization.

**INHALATION:** High vapor/aerosol concentrations (>1000 ppm) are irritating to the eyes and respiratory tract.

**INGESTION:** May be harmful or fatal if swallowed. Corrosive. May cause severe burns and complete tissue perforation of mucous membranes, mouth, throat and stomach.

**Target Organ Effects:** Liver, kidney, lungs and upper respiratory tract, gastrointestinal tract, eyes, skin.

**Reproductive/Developmental Information:** 2-Butoxyethanol has caused red blood cell hemolysis in lab animals and secondary injury to the liver and kidney.

**Carcinogenic Information:** This material is not listed as a carcinogen by IARC, NTP or OSHA.

**Acute Toxicity Values:**

2-butoxyethanol: Ingestion - LD50, rat, 1300 mg/Kg; Dermal LD50, guinea pig 1400 mg/Kg; Inhalation - LC50, 1 hr, vapor, guineapig > 3.1 mg/l

## Section 12 Ecological Information

2-butoxyethanol: EC50, Daphnia magna, static test, 48 h, immobilization: 1550 mg/l

Bluegill sunfish, static test, 96 h, 1300 mg/l.

## Section 13 Disposal Considerations

Waste must be disposed of in accordance with federal, state and local environmental control regulations. See label for further instructions.

## Section 14 Transport Information

Certain shipping modes or package sizes may have exceptions from the transport regulations. The classification provided may not reflect those exceptions and may not apply to all shipping modes or package sizes.

<b>UN number</b>	1950
<b>Proper shipping name</b>	Aerosols, nonflammable
<b>Class</b>	2.2
<b>Packing group</b>	-

## Section 15 Regulatory Information

### Section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 (40 CFR 372.65)

2-butoxyethanol

If identified components of this product are **CERCLA** hazardous substances and/or listed under **Sections 302, 304, or 313 of Title III** of the Superfund Amendments and Reauthorization Act (SARA) of 1986 (also known as EPCRA, the Emergency Planning and Community Right-To-Know Act), or under **California Proposition 65** (Safe Drinking Water and Toxic Enforcement Act), they are listed above in Section 15 of this SDS.

If identified components of this product are listed under Section 313, this product contains toxic chemicals subject to the reporting requirements of Section 313. This information must be included in all SDS that are copied and distributed for this material.

### **Title III Section 311/312** Hazardous Categories - 40 CFR 370.2:

ACUTE (X) Chronic ( ) Fire ( ) Pressure (X) Reactive ( ) Not Applicable ( )

**T.S.C.A. Status:** All chemical substances found in this product comply with the Toxic Substances Control Act inventory reporting requirements.

**RCRA Status:** Under RCRA, it is the responsibility of the product user to determine at the time of disposal, whether a material containing the product or derived from the product should be classified as a hazardous waste. If this product becomes hazardous waste it would be assigned RCRA Code(s)

D002

## Section 16 Other Information

### HMIS Ratings :

<b>HEALTH</b>	1
<b>FLAMMABILITY</b>	4
<b>REACTIVITY</b>	0
<b>PERSONAL PROTECTION</b>	B

**Relevant Phrases (code & fill text)**

**H226 - Flammable liquid and vapour - H302 - Harmful if swallowed**

**H315 - May Cause skin irritation - H317 May cause an allergic skin reaction**

**H381 - May Cause serious eye damage - H319 - May cause serious eye irritation**

**H335- May cause respiration irritation - R10- Flammable**

**R36/37/38 - Irritating to eyes, respiratory system and skin**

**R41- Risk of serious damage to eyes**

**R43 - May cause sensitization by skin contact**

**Last Revision Date: 1/July/2020**

Disclaimer: The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text herein. It is the responsibility of the end user to determine the applicability and use of this material prior to its use.

Consult with your HSE officer prior to the use of this or any other product. Always wear the proper PPE when handling chemicals.